Refine Search

Search Results -

Terms	Documents
L2 same interfac$3	27

Database:
US Pre-Grant Publication Full-Text Database
US Patents Full-Text Database
US OCR Full-Text Database
EPO Abstracts Database
JPO Abstracts Database
Derwent World Patents Index
IBM Technical Disclosure Bulletins

Search: L3

[Refine Search]

[Recall Text] [Clear] [Interrupt]

Search History

DATE: Friday, June 24, 2005 Printable Copy Create Case

Set Name	Query	Hit Count	Set Name
side by side			result set
	DB=PGPB,USPT,USOC; PLUR=YES; OP=OR		
L3	L2 same interfac$3	27	L3
L2	primary same secondary same function same monitor$3 same bus	141	L2
L1	"primary function" same "secondary function" same monitor$3 same bus	1	L1

END OF SEARCH HISTORY

Refine Search

Search Results -

Terms	Documents
(702/122 |702/190 |713/153 |713/154 |709/224 |709/217 |709/249 |370/245 |370/252 |370/451 |710/305 |710/105 |710/15 |714/47 |714/799).ccls.	15025

Database:

US Pre-Grant Publication Full-Text Database
US Patents Full-Text Database
US OCR Full-Text Database
EPO Abstracts Database
JPO Abstracts Database
Derwent World Patents Index
IBM Technical Disclosure Bulletins

Search: L1

[Refine Search]

[Recall Text] [Clear] [Interrupt]

Search History

DATE: **Friday, June 24, 2005**   Printable Copy   Create Case

Set Name side by side	Query	Hit Count	Set Name result set
DB=PGPB,USPT,USOC; PLUR=YES; OP=OR			
L1	710/305,105,15;709/224,217,249;370/245,252,451;713/153,154;702/122,190;714/47,799.ccls.	15025	L1

END OF SEARCH HISTORY

Refine Search

Search Results -

Terms	Documents
L1 and L2	6

Database:

US Pre-Grant Publication Full-Text Database
US Patents Full-Text Database
US OCR Full-Text Database
EPO Abstracts Database
JPO Abstracts Database
Derwent World Patents Index
IBM Technical Disclosure Bulletins

Search:

L3

| Refine Search |

| Recall Text ⬍ | | Clear | | Interrupt |

Search History

DATE: Friday, June 24, 2005   Printable Copy   Create Case

Set Name side by side	Query	Hit Count	Set Name result set
	DB=PGPB,USPT,USOC; PLUR=YES; OP=OR		
L3	l1 and L2	6	L3
L2	(primary adj5 function) same (secondary adj5 function) same monitor$3	84	L2
L1	710/305,105,15;709/224,217,249;370/245,252,451;713/153,154;702/122,190;714/47,799.ccls.	15025	L1

END OF SEARCH HISTORY

Refine Search

Search Results -

Terms	Documents
(primary adj1 function) same (secondary adj5 function) same monitor$3	2

Database:

US Pre-Grant Publication Full-Text Database
US Patents Full-Text Database
US OCR Full-Text Database
EPO Abstracts Database
JPO Abstracts Database
Derwent World Patents Index
IBM Technical Disclosure Bulletins

Search:

L1

Refine Search

Recall Text   Clear   Interrupt

Search History

DATE: Friday, June 24, 2005   Printable Copy   Create Case

Set Name Query   **Hit Count Set Name**
side by side   result set
DB=EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=OR

L1   (primary adj1 function) same (secondary adj5 function) same monitor$3   2   L1

END OF SEARCH HISTORY

EAST - [Untitled1:1]

File View Edit Tools Window Help

- Drafts
- Pending
- **Active**
  - L1: (116) (primary near
  - L2: (10) l1 same bus
- Failed
- Saved
- Favorites
- Tagged (0)
- UDC
- Queue
- Trash

Search List Prixer Queue Alter

DBs USPAT

Default operator OR

☑ Plurals
☑ Highlight all hit terms initially

BRS form IS&R form Image Text HTML

	Type	L #	Hits	Search Text	DBs	Time Stam	Comment	Error	Definit	Er
1	BRS	L1	116	(primary near5 function) same (secon	USPA T	2005/06/2 4 09:09				
2	BRS	L2	10	l1 same bus	USPA T	2005/06/2 4 09:09				

Start EAST - [...

EAST - [Untitled1:1]

File View Edit Tools Window Help

- Drafts
- Pending
- Active
  - L1: (116) (primary near
  - L2: (10) l1 same bus
- Failed
- Saved
- Favorites
- Tagged (0)
- UDC
- Queue
- Trash

Search | | Browse | | Clear

DBs USPAT ☑ Plurals

Default operator OR ▼ ☑ Highlight all hit terms initially

l1 same bus

BRS form IS&R form Image Text HTML

	U	1	Document ID	Issue Dat	Pages	Title	Current OR	Current XR
1	☐	☐	US 6286048 B1	20010904	11	System and method for discovering relative st	709/225	
2	☐	☐	US 6230089 B1	20010508	21	Turf maintenance vehicle multiple contro	701/48	701/33; 701/36;
3	☐	☐	US 5809220 A	19980915	17	Fault tolerant distributed control sys	714/12	714/55
4	☐	☐	US 5796935 A	19980818	19	Voting node for a distributed control sys	714/11	714/797
5	☑	☐	US 5706278 A	19980106	18	Deterministic network protocol	370/222	370/443; 370/452;
6	☑	☐	US 5634025 A	19970527	26	Method and system for efficiently fetching va	712/207	
7	☑	☐	US 4190863 A	19800226	19	Remote control system for a television camera	348/211.5	
8	☑	☐	US 4170024 A	19791002	20	Television control system	348/211.14	
9	☑	☐	US 4167022 A	19790904	20	Setup control unit for television cameras	348/188	348/211.7; 348/722
10	☐	☐	US 4158208 A	19790612	18	Automatic setup system for television cameras	348/176	348/207.99 ;

Start | EAST - [...

Welcome United States Patent and Trademark Office

Search Results   BROWSE   SEARCH   IEEE XPLORE GUIDE   SUPPORT

Results for "((primary function) and (secondary function)<in>metadata)"   ✉ e-mail   🖨 printer friendly
Your search matched **2** of **1174497** documents.
A maximum of **100** results are displayed, **25** to a page, sorted by **Relevance** in **Descending** order.

» View Session History

» New Search

» **Key**

IEEE JNL	IEEE Journal or Magazine
IEE JNL	IEE Journal or Magazine
IEEE CNF	IEEE Conference Proceeding
IEE CNF	IEE Conference Proceeding
IEEE STD	IEEE Standard

Modify Search

((primary function) and (secondary function)<in>metadata)   ≫

☐ Check to search only within this results set

Display Format: ● Citation   ○ Citation & Abstract

Select   Article Information

☐   1. **Leak checker data acquisition system**
Payne, J.; Gannon, J.;
Particle Accelerator Conference, 1993., Proceedings of the 1993
17-20 May 1993 Page(s):3870 - 3872 vol.5

AbstractPlus | Full Text: PDF(344 KB)   IEEE CNF

☐   2. **Space Shuttle RTOS Bayesian network**
Morris, A.T.; Beling, P.A.;
Digital Avionics Systems, 2001. DASC. The 20th Conference
Volume 1, 14-18 Oct. 2001 Page(s):4D5/1 - 4D5/13 vol.1

AbstractPlus | Full Text: PDF(970 KB)   IEEE CNF

Help   Contact Us   Privacy & Security   IEEE.org

Indexed by
Inspec

IEEE Xplore

RELEASE 2.0

AbstractPlus

◄ View Search Results | Next Article ►

Access this document

Full Text: PDF (344 KB)

Download this citation

Choose   Citation

Download EndNote, ProCite, RefMan

Rights & Permissions

RIGHTS (Request Permissions)

» Learn More

» Learn More

Leak checker data acquisition system

Payne, J. Gannon, J.;
Dept. of Electr. Eng., SSC Lab., Dallas, TX, USA;

This paper appears in: **Particle Accelerator Conference, 1993, Proceedings of the 1993**
Publication Date: 17-20 May 1993
On page(s): 3870 - 3872 vol.5
Meeting Date: 05/17/1993 - 05/20/1993
Location: Washington, DC
INSPEC Accession Number:4795348
DOI: 10.1109/PAC.1993.309796
Posted online: 2002-08-06 18:59:02.0

Abstract
A portable, high speed, computerized, data logging system is proposed. The **primary function** of this system is to collect 'helium readings' from mass spectrometers. This system monitors up to 14 mass spectrometers, operating from as far away as 1 kilometer, or clustered to isolate a helium leak within 20 cm. Data logging enables technicians to witness the flight of the helium through the magnet string by a graphical plotting of every channel within microseconds of when the helium was released into the vacuum. The readings are used to locate vacuum leaks and provide acceptance testing of the vacuum system for a string of superconducting magnets. The **secondary functions of** this system are the documentation of test conditions, archiving data sets for future reference, and providing a real-time display of all channels as the string of magnets approach critical test conditions

Index Terms
Inspec

Controlled Indexing
He He leak He readings acceptance testing computerized data logging system data acquisition data acquisition system data loggers leak checker leak detection mass spectrometers mass spectroscopy spectroscopy computing vacuum leaks vacuum system

Non-controlled Indexing
He He leak He readings acceptance testing computerized data logging system data acquisition data acquisition system data loggers leak checker leak detection mass spectrometers mass spectroscopy spectroscopy computing vacuum leaks vacuum system

Author Keywords
Not Available

References

No references available on IEEE Xplore.

Citing Documents

No citing documents available on IEEE Xplore.

Help   Contact Us   Privacy & Security   IEEE.org

Hit List

Search Results - Record(s) 1 through 6 of 6 returned.

☐ 1. Document ID: US 20050076151 A1

L3: Entry 1 of 6   File: PGPB   Apr 7, 2005

PGPUB-DOCUMENT-NUMBER: 20050076151
PGPUB-FILING-TYPE: new
DOCUMENT-IDENTIFIER: US 20050076151 A1

TITLE: Wireless bridge device within a process control system

PUBLICATION-DATE: April 7, 2005

INVENTOR-INFORMATION:

NAME	CITY	STATE	COUNTRY	RULE-47
Tapperson, Gary	Austin	TX	US	
Boyd, Thomas Andrew	Austin	TX	US	

US-CL-CURRENT: 709/249

| Full | Title | Citation | Front | Review | Classification | Date | Reference | Sequences | Attachments | Claims | KWIC | Draw Desc | Image |

☐ 2. Document ID: US 20040139264 A1

L3: Entry 2 of 6   File: PGPB   Jul 15, 2004

PGPUB-DOCUMENT-NUMBER: 20040139264
PGPUB-FILING-TYPE: new
DOCUMENT-IDENTIFIER: US 20040139264 A1

TITLE: Bus station with integrated bus monitor function

PUBLICATION-DATE: July 15, 2004

INVENTOR-INFORMATION:

NAME	CITY	STATE	COUNTRY	RULE-47
Gros, Thomas	Neustadt		DE	
Faist, Fridolin	Oberwolfach		DE	

US-CL-CURRENT: 710/305

| Full | Title | Citation | Front | Review | Classification | Date | Reference | Sequences | Attachments | Claims | KWIC | Draw Desc | Image |

☐ 3. Document ID: US 6327620 B1

L3: Entry 3 of 6   File: USPT   Dec 4, 2001

US-PAT-NO: 6327620
DOCUMENT-IDENTIFIER: US 6327620 B1

TITLE: Methods and apparatus for collecting, storing, processing and using network traffic data

Full	Title	Citation	Front	Review	Classification	Date	Reference			Claims	KWIC	Draw Desc	Image

☐ 4. Document ID: US 6279037 B1

L3: Entry 4 of 6   File: USPT   Aug 21, 2001

US-PAT-NO: 6279037
DOCUMENT-IDENTIFIER: US 6279037 B1

TITLE: Methods and apparatus for collecting, storing, processing and using network traffic data

Full	Title	Citation	Front	Review	Classification	Date	Reference			Claims	KWIC	Draw Desc	Image

☐ 5. Document ID: US 5793963 A

L3: Entry 5 of 6   File: USPT   Aug 11, 1998

US-PAT-NO: 5793963
DOCUMENT-IDENTIFIER: US 5793963 A

TITLE: Apparatus for providing non-redundant secondary access to field devices in a distributed control system

Full	Title	Citation	Front	Review	Classification	Date	Reference			Claims	KWIC	Draw Desc	Image

☐ 6. Document ID: US 5699348 A

L3: Entry 6 of 6   File: USPT   Dec 16, 1997

US-PAT-NO: 5699348
DOCUMENT-IDENTIFIER: US 5699348 A

TITLE: Method and apparatus for error performance monitoring of a leased telecommunication circuit

Full	Title	Citation	Front	Review	Classification	Date	Reference			Claims	KWIC	Draw Desc	Image

Clear	Generate Collection	Print	Fwd Refs	Bkwd Refs	Generate OACS

Terms	Documents
L1 and L2	6

Display Format: |- [ ] Change Format

Hit List

Search Results - Record(s) 1 through 10 of 27 returned.

☐ 1. Document ID: US 20050057224 A1

L3: Entry 1 of 27   File: PGPB   Mar 17, 2005

PGPUB-DOCUMENT-NUMBER: 20050057224
PGPUB-FILING-TYPE: new
DOCUMENT-IDENTIFIER: US 20050057224 A1

TITLE: Alternating-source peak-shift power application system, method and program product

PUBLICATION-DATE: March 17, 2005

INVENTOR-INFORMATION:

NAME	CITY	STATE	COUNTRY	RULE-47
Naitoh, Arimasa	Fujisawa-shi		JP	
Odaohhara, Shigefumi	Yamato-shi		JP	

US-CL-CURRENT: 320/128

| Full | Title | Citation | Front | Review | Classification | Date | Reference | Sequences | Attachments | Claims | KWIC | Draw Desc | Image |

☐ 2. Document ID: US 20040239173 A1

L3: Entry 2 of 27   File: PGPB   Dec 2, 2004

PGPUB-DOCUMENT-NUMBER: 20040239173
PGPUB-FILING-TYPE: new
DOCUMENT-IDENTIFIER: US 20040239173 A1

TITLE: Redundant architecture for brake-by-wire system

PUBLICATION-DATE: December 2, 2004

INVENTOR-INFORMATION:

NAME	CITY	STATE	COUNTRY	RULE-47
Williams, Aaron Charles	Hinesburg	VT	US	
Ash, Bryan Antony	Bristol	VT	US	
Conklin, Peter Stanton	South Burlington	VT	US	
Zwick, David	Pittsford	NY	US	
Townsend, David	Montreal		CA	

US-CL-CURRENT: 303/3

| Full | Title | Citation | Front | Review | Classification | Date | Reference | Sequences | Attachments | Claims | KWIC | Draw Desc | Image |

3. Document ID: US 20040215569 A1

L3: Entry 3 of 27   File: PGPB   Oct 28, 2004

PGPUB-DOCUMENT-NUMBER: 20040215569
PGPUB-FILING-TYPE: new
DOCUMENT-IDENTIFIER: US 20040215569 A1

TITLE: Method to ensure a unique machine serial number

PUBLICATION-DATE: October 28, 2004

INVENTOR-INFORMATION:

NAME	CITY	STATE	COUNTRY	RULE-47
Agha, Salim Ahmed	Rochester	MN	US	
Birkestrand, Daniel Charles	Rochester	MN	US	
Igel, Stephen Mark	Rochester	MN	US	
Lewis, David Otto	Rochester	MN	US	

US-CL-CURRENT: 705/57

| Full | Title | Citation | Front | Review | Classification | Date | Reference | Sequences | Attachments | Claims | KWIC | Draw Desc | Image |

4. Document ID: US 20040139264 A1

L3: Entry 4 of 27   File: PGPB   Jul 15, 2004

PGPUB-DOCUMENT-NUMBER: 20040139264
PGPUB-FILING-TYPE: new
DOCUMENT-IDENTIFIER: US 20040139264 A1

TITLE: Bus station with integrated bus monitor function

PUBLICATION-DATE: July 15, 2004

INVENTOR-INFORMATION:

NAME	CITY	STATE	COUNTRY	RULE-47
Gros, Thomas	Neustadt		DE	
Faist, Fridolin	Oberwolfach		DE	

US-CL-CURRENT: 710/305

| Full | Title | Citation | Front | Review | Classification | Date | Reference | Sequences | Attachments | Claims | KWIC | Draw Desc | Image |

5. Document ID: US 20030216969 A1

L3: Entry 5 of 27   File: PGPB   Nov 20, 2003

PGPUB-DOCUMENT-NUMBER: 20030216969
PGPUB-FILING-TYPE: new
DOCUMENT-IDENTIFIER: US 20030216969 A1

TITLE: Inventory management system

PUBLICATION-DATE: November 20, 2003

INVENTOR-INFORMATION:

NAME	CITY	STATE	COUNTRY	RULE-47
Bauer, Donald G.	Laurel	MD	US	
Campero, Richard J.	Ellicott City	MD	US	
Rasband, Paul B.	Frederick	MD	US	
Weel, Martin D.	Coto De Caza	CA	US	

US-CL-CURRENT: 705/22; 235/385, 340/5.92

| Full | Title | Citation | Front | Review | Classification | Date | Reference | Sequences | Attachments | Claims | KWIC | Draw Desc | Image |

☐ 6.   Document ID: US 20030204657 A1

L3: Entry 6 of 27   File: PGPB   Oct 30, 2003

PGPUB-DOCUMENT-NUMBER: 20030204657
PGPUB-FILING-TYPE: new
DOCUMENT-IDENTIFIER: US 20030204657 A1

TITLE: Method and apparatus for BIOS control of electrical device address/identification assignments

PUBLICATION-DATE: October 30, 2003

INVENTOR-INFORMATION:

NAME	CITY	STATE	COUNTRY	RULE-47
Lehwalder, Philip R.	Portland	OR	US	
Barmore, Brad A.	Portland	OR	US	

US-CL-CURRENT: 710/301

| Full | Title | Citation | Front | Review | Classification | Date | Reference | Sequences | Attachments | Claims | KWIC | Draw Desc | Image |

☐ 7.   Document ID: US 20020065582 A1

L3: Entry 7 of 27   File: PGPB   May 30, 2002

PGPUB-DOCUMENT-NUMBER: 20020065582
PGPUB-FILING-TYPE: new
DOCUMENT-IDENTIFIER: US 20020065582 A1

TITLE: Electro-statically-shielded processing module

PUBLICATION-DATE: May 30, 2002

INVENTOR-INFORMATION:

NAME	CITY	STATE	COUNTRY	RULE-47
Morrison, Brian D.	Hopkinton	MA	US	
Connolly, Paul A.	Milford	MA	US	

US-CL-CURRENT: 700/286; 700/22, 73/1.35

`Full | Title | Citation | Front | Review | Classification | Date | Reference | Sequences | Attachments | Claims | KWIC | Draw Desc | Image`

☐ 8.   Document ID: US 6826715 B1

L3: Entry 8 of 27   File: USPT   Nov 30, 2004

US-PAT-NO: 6826715
DOCUMENT-IDENTIFIER: US 6826715 B1

TITLE: Automatic capture and comparison of computer configuration data

`Full | Title | Citation | Front | Review | Classification | Date | Reference |        |        | Claims | KWIC | Draw Desc | Image`

☐ 9.   Document ID: US 6807149 B1

L3: Entry 9 of 27   File: USPT   Oct 19, 2004

US-PAT-NO: 6807149
DOCUMENT-IDENTIFIER: US 6807149 B1

TITLE: Method and system for LEC resiliency with fast failover

`Full | Title | Citation | Front | Review | Classification | Date | Reference |        |        | Claims | KWIC | Draw Desc | Image`

☐ 10.   Document ID: US 6601190 B1

L3: Entry 10 of 27   File: USPT   Jul 29, 2003

US-PAT-NO: 6601190
DOCUMENT-IDENTIFIER: US 6601190 B1

TITLE: Automatic capture and reporting of computer configuration data

`Full | Title | Citation | Front | Review | Classification | Date | Reference |        |        | Claims | KWIC | Draw Desc | Image`

`Clear`   `Generate Collection`   `Print`   `Fwd Refs`   `Bkwd Refs`   `Generate OACS`

Terms	Documents
L2 same interfac$3	27

Display Format: `-` `Change Format`

Previous Page   Next Page   Go to Doc#

Hit List

Search Results - Record(s) 11 through 20 of 27 returned.

☐ 11. Document ID: US 6600972 B2

L3: Entry 11 of 27   File: USPT   Jul 29, 2003

US-PAT-NO: 6600972
DOCUMENT-IDENTIFIER: US 6600972 B2

TITLE: Electro-statically-shielded processing module

| Full | Title | Citation | Front | Review | Classification | Date | Reference | | | Claims | KWIC | Draw Desc | Image |

☐ 12. Document ID: US 6426957 B1

L3: Entry 12 of 27   File: USPT   Jul 30, 2002

US-PAT-NO: 6426957
DOCUMENT-IDENTIFIER: US 6426957 B1

TITLE: Asynchronous transfer mode based service consolidation switch

| Full | Title | Citation | Front | Review | Classification | Date | Reference | | | Claims | KWIC | Draw Desc | Image |

☐ 13. Document ID: US 6356809 B1

L3: Entry 13 of 27   File: USPT   Mar 12, 2002

US-PAT-NO: 6356809
DOCUMENT-IDENTIFIER: US 6356809 B1
** See image for **Certificate of Correction** **.

TITLE: Electro-statically shielded processing module

| Full | Title | Citation | Front | Review | Classification | Date | Reference | | | Claims | KWIC | Draw Desc | Image |

☐ 14. Document ID: US 6314523 B1

L3: Entry 14 of 27   File: USPT   Nov 6, 2001

US-PAT-NO: 6314523
DOCUMENT-IDENTIFIER: US 6314523 B1

TITLE: Apparatus for distributing power to a system of independently powered devices

| Full | Title | Citation | Front | Review | Classification | Date | Reference | | | Claims | KWIC | Draw Desc | Image |

☐ 15. Document ID: US 6295090 B1

L3: Entry 15 of 27   File: USPT   Sep 25, 2001

US-PAT-NO: 6295090
DOCUMENT-IDENTIFIER: US 6295090 B1

TITLE: Apparatus for providing video resolution compensation when converting one video source to another video source

| Full | Title | Citation | Front | Review | Classification | Date | Reference | | | Claims | KWIC | Draw Desc | Image |

☐ 16. Document ID: US 6201580 B1

L3: Entry 16 of 27   File: USPT   Mar 13, 2001

US-PAT-NO: 6201580
DOCUMENT-IDENTIFIER: US 6201580 B1
** See image for Certificate of Correction **

TITLE: Apparatus for supporting multiple video resources

| Full | Title | Citation | Front | Review | Classification | Date | Reference | | | Claims | KWIC | Draw Desc | Image |

☐ 17. Document ID: US 6157464 A

L3: Entry 17 of 27   File: USPT   Dec 5, 2000

US-PAT-NO: 6157464
DOCUMENT-IDENTIFIER: US 6157464 A

TITLE: Facsimile store and forward system with local interface

| Full | Title | Citation | Front | Review | Classification | Date | Reference | | | Claims | KWIC | Draw Desc | Image |

☐ 18. Document ID: US 6044207 A

L3: Entry 18 of 27   File: USPT   Mar 28, 2000

US-PAT-NO: 6044207
DOCUMENT-IDENTIFIER: US 6044207 A

TITLE: Enhanced dual port I/O bus bridge

| Full | Title | Citation | Front | Review | Classification | Date | Reference | | | Claims | KWIC | Draw Desc | Image |

☐ 19. Document ID: US 5930237 A

L3: Entry 19 of 27   File: USPT   Jul 27, 1999

US-PAT-NO: 5930237
DOCUMENT-IDENTIFIER: US 5930237 A

TITLE: Video conference system with ATM cell reuse

| Full | Title | Citation | Front | Review | Classification | Date | Reference | | | Claims | KWIC | Draw Desc | Image |

☐ 20.   Document ID: US 5850395 A

   L3: Entry 20 of 27   File: USPT   Dec 15, 1998

US-PAT-NO: 5850395
DOCUMENT-IDENTIFIER: US 5850395 A
** See image for **Certificate of Correction** **

TITLE: Asynchronous transfer mode based service consolidation switch

| Full | Title | Citation | Front | Review | Classification | Date | Reference | | | Claims | KWIC | Draw Desc | Image |

| Clear | Generate Collection | Print | Fwd Refs | Bkwd Refs | Generate OACS |

Terms	Documents
L2 same interfac$3	27

Display Format: |- | Change Format

Previous Page   Next Page   Go to Doc#

Hit List

Clear	Generate Collection	Print	Fwd Refs	Bkwd Refs	Generate OACS

Search Results - Record(s) 21 through 27 of 27 returned.

☐ 21. Document ID: US 5559611 A

L3: Entry 21 of 27   File: USPT   Sep 24, 1996

US-PAT-NO: 5559611
DOCUMENT-IDENTIFIER: US 5559611 A

TITLE: Facsimile store and forward system with local interface

Full	Title	Citation	Front	Review	Classification	Date	Reference			Claims	KWIC	Draw Desc	Image

---

☐ 22. Document ID: US 5555100 A

L3: Entry 22 of 27   File: USPT   Sep 10, 1996

US-PAT-NO: 5555100
DOCUMENT-IDENTIFIER: US 5555100 A

TITLE: Facsimile store and forward system with local interface translating DTMF signals into store and forward system commands

Full	Title	Citation	Front	Review	Classification	Date	Reference			Claims	KWIC	Draw Desc	Image

---

☐ 23. Document ID: US 5517631 A

L3: Entry 23 of 27   File: USPT   May 14, 1996

US-PAT-NO: 5517631
DOCUMENT-IDENTIFIER: US 5517631 A

TITLE: Miniature disk drive having embedded sector servo with split data fields and automatic on-the-fly data block sequencing

Full	Title	Citation	Front	Review	Classification	Date	Reference			Claims	KWIC	Draw Desc	Image

---

☐ 24. Document ID: US 4805171 A

L3: Entry 24 of 27   File: USPT   Feb 14, 1989

US-PAT-NO: 4805171
DOCUMENT-IDENTIFIER: US 4805171 A

TITLE: Unitary PCM rate converter and multiframe buffer

Full	Title	Citation	Front	Review	Classification	Date	Reference			Claims	KWIC	Draw Desc	Image

☐ 25. Document ID: US 4695944 A

L3: Entry 25 of 27   File: USPT   Sep 22, 1987

US-PAT-NO: 4695944
DOCUMENT-IDENTIFIER: US 4695944 A

TITLE: Computer system comprising a data, address and control signal bus which comprises a left bus and a right bus

| Full | Title | Citation | Front | Review | Classification | Date | Reference | | | Claims | KWIC | Draw Desc | Image |

☐ 26. Document ID: US 4489438 A

L3: Entry 26 of 27   File: USPT   Dec 18, 1984

US-PAT-NO: 4489438
DOCUMENT-IDENTIFIER: US 4489438 A

TITLE: Audio response system

| Full | Title | Citation | Front | Review | Classification | Date | Reference | | | Claims | KWIC | Draw Desc | Image |

☐ 27. Document ID: US 3432841 A

L3: Entry 27 of 27   File: USOC   Mar 11, 1969

US-PAT-NO: 3432841
DOCUMENT-IDENTIFIER: US 3432841 A

TITLE: STATUS INDICATING AND ALARM ANNUNCIATING SYSTEMS FOR ELECTRICALLY POWERED DEVICES

DATE-ISSUED: March 11, 1969

INVENTOR-NAME: CLAY CHARLES L; HARVEY HERBERT ; SIMS MARTIN H

US-CL-CURRENT: 340/635, 340/654, 361/23

| Full | Title | Citation | Front | Review | Classification | Date | Reference | | | Claims | KWIC | Draw Desc | Image |

| Clear | Generate Collection | Print | Fwd Refs | Bkwd Refs | Generate OACS |

Terms	Documents
L2 same interfac$3	27

Display Format: |- | Change Format

Previous Page   Next Page   Go to Doc#

☐ Generate Collection | Print |

L3: Entry 25 of 27   File: USPT   Sep 22, 1987

US-PAT-NO: 4695944
DOCUMENT-IDENTIFIER: US 4695944 A

TITLE: Computer system comprising a data, address and control signal bus which comprises a left bus and a right bus

DATE-ISSUED: September 22, 1987

INVENTOR-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY
Zandveld; Frederik	Beekbergen			NL
Visser; Jeroen M.	Beekbergen			NL

ASSIGNEE-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY	TYPE CODE
U.S. Philips Corporation	New York	NY			02

APPL-NO: 06/ 910796   [PALM]
DATE FILED: September 22, 1986

PARENT-CASE:
This is a continuation of application Ser. No. 495,379, filed May 17, 1983, now abandoned.

FOREIGN-APPL-PRIORITY-DATA:

COUNTRY	APPL-NO	APPL-DATE
NL	8202060	May 19, 1982

INT-CL: [04] G06F 13/14, G06F 13/38

US-CL-ISSUED: 364/200
US-CL-CURRENT: 710/105

FIELD-OF-SEARCH: 364/2MSFile, 364/9MSFile

PRIOR-ART-DISCLOSED:

U.S. PATENT DOCUMENTS

| Search Selected | Search ALL | Clear |

	PAT-NO	ISSUE-DATE	PATENTEE-NAME	US-CL
☐	4047162	September 1977	Dorey et al.	364/900
☐	4106104	August 1978	Nitta et al.	364/900
☐	4231086	October 1980	Tarbox et al.	364/200
☐	4257099	March 1981	Appelt	364/200

	4320451	March 1982	Bachman et al.	364/200
	4380798	April 1983	Shannon et al.	364/200
	4390943	June 1983	Twibell et al.	364/200
	4442504	April 1984	Dummermuth et al.	364/900

OTHER PUBLICATIONS

Madnick, "Operation System", pp. 255-261, 1974, McGraw-Hill.

ART-UNIT: 232

PRIMARY-EXAMINER: Eng; David Y.

ATTY-AGENT-FIRM: Haken; Jack E. Cannon, Jr.; James J.

ABSTRACT:

A computer system comprises a bus for data, address and control signals which is divided into a left bus and a right bus by a first gating device. The gating device has an open state which is character-wise activated by a right bus request transported on the left bus. Furthermore, the gating device conducts start signals from a processor station connected to the left bus and interrupt signals from a peripheral apparatus connected to the right bus. In the closed state of the gating device, bulk data transport is possible on the right bus without interfering with the processor station. The processing speed is thus increased.

7 Claims, 7 Drawing figures

Previous Doc   Next Doc   Go to Doc#

☐ ▨▨▨▨ Generate Collection ▨▨▨▨ | Print |

L1: Entry 1 of 1   File: PGPB   Jul 15, 2004

DOCUMENT-IDENTIFIER: US 20040139264 A1
TITLE: Bus station with integrated bus monitor function

Summary of Invention Paragraph:
[0020] This problem is solved according to a first aspect of the invention by a newly designed
bus station such as a sensor, an actuator, a control unit or a gateway, etc. combining the
primary function of each device with a secondary function, i.e. the bus monitor function, by
integrating a bus monitoring means in the bus station. In the context of the present invention,
the primary function refers to the main purpose of each bus station, i.e. the device to be
coupled to the bus for which it is used. For example, the primary function of a sensor is to
detect physical processes and to convert them into electrical or digital signals that may be
further processed and evaluated. According to the invention, each bus station, apart from this
primary function, also uses the bus interface, already present for the purposes of process data
communication, to carry out the monitoring of the bus system as a secondary task.

CLAIMS:

1. A bus station having a primary function such as a sensor function and that may be coupled to
a bus system, comprising: at least one bus interface for communication of said bus station with
said bus system, and a bus monitor means integrated with said bus station and coupled to said
bus interface, said bus monitor means giving said bus station a secondary function, wherein
said bus monitor means is adapted for at least one of the following activities: monitoring of
the communication of said bus station with said bus system via said bus interface, and
monitoring of the internal communication within said bus station.

23. A network having at least one bus system and at least one bus station having a primary
function, such as a sensor function, and which may be coupled to a bus system, wherein said bus
station comprises at least one bus interface for communication of said bus station with said
bus system, and a bus monitor means; wherein said bus monitor means is integrated with said bus
station and coupled to said bus interface, and giving said bus station a secondary function,
wherein said bus monitor means is adapted for monitoring of the communication of said bus
station with said bus system via said bus interface, wherein said network is monitored by means
of said bus monitor means integrated with said bus station.

24. A method for carrying out monitoring processes of a bus system, comprising: coupling a bus
station to said bus system, wherein said bus station has a primary function such as a sensor
function, and comprising at least one bus interface for communication of said bus station with
said bus system, and a bus monitor means; wherein said bus monitor means is integrated with
said bus station and coupled to said bus interface, wherein said bus monitor means gives a
secondary function to said bus station in the form of said monitoring, monitoring the
communication of said bus station with said bus system via said bus interface by means of said
bus monitor means.

27. A method for carrying out monitoring processes of a bus system, comprising: coupling a bus
station to said bus system, wherein said bus station has a primary function such as a sensor
function, and comprising at least one bus interface for communication of said bus station with
said bus system, and a bus monitor means; wherein said bus monitor means is integrated with
said bus station and coupled to said bus interface, wherein said bus monitor means gives a
secondary function to said bus station in the form of said monitoring, monitoring the internal
communication of said bus station by means of said bus monitor means.

☐ ▓▓▓ Generate Collection ▓▓▓ │ Print │

L1: Entry 1 of 1   File: PGPB   Jul 15, 2004

PGPUB-DOCUMENT-NUMBER: 20040139264
PGPUB-FILING-TYPE: new
DOCUMENT-IDENTIFIER: US 20040139264 A1

TITLE: Bus station with integrated bus monitor function

PUBLICATION-DATE: July 15, 2004

INVENTOR-INFORMATION:

NAME	CITY	STATE	COUNTRY	RULE-47
Gros, Thomas	Neustadt		DE	
Faist, Fridolin	Oberwolfach		DE	

APPL-NO: 10/ 623199   [PALM]
DATE FILED: July 18, 2003

RELATED-US-APPL-DATA:
Application is a non-provisional-of-provisional application 60/397558, filed July 18, 2002,

INT-CL: [07] G06 F 13/14

US-CL-PUBLISHED: 710/305
US-CL-CURRENT: 710/305

REPRESENTATIVE-FIGURES: 1

ABSTRACT:

The present invention relates to a bus station (14; 15; 23) such as a sensor (14), an actuator (15) or a gateway (23) fulfilling, apart from their primary device immanent function, a secondary function, namely a bus monitor function. In order to be able to fulfil said secondary function, the bus stations (14; 15; 23) are each equipped with a bus monitor means (30) which makes it possible to access, to detect and to further process the telegram traffic carried on the bus system (5; 40). The invention also relates to a network equipped with such bus stations (14; 15; 23) and a method for carrying out such monitoring with the aid of said bus stations (14; 15; 23).

PRIORITY CLAIM

[0001] This application claims the benefit of U.S. Provisional Patent Application Serial No. 60/397,558 filed on Jul. 18, 2002 which is expressly incorporated herein, in its entirety, by reference.

File Edit View Tools Window Help

US-PAT-NO: 5809220

DOCUMENT-IDENTIFIER: US 5809220 A

TITLE: Fault tolerant distributed control system

---------- KWIC ----------

Detailed Description Text - DETX (2):
   Referring to FIG. 1, a block diagram of a distributed intelligence fault
tolerant control-by-light.TM. system 10 is shown comprising a deterministic
network protocol for communication with a plurality of intelligent nodes 12,
14, 16, 18, 20. Such nodes 12-20 are connected to one or more bi-directional
serial buses 21, 22, 23, each of said buses being a single fiber optic ring in
the preferred embodiment. The number of nodes shown in FIG. 1 is only
representative of a system and one skilled in the art will recognize that many
node configurations are feasible depending on the particular system
application. The system 10 is particularly useful for aircraft control by
providing a low cost fault-tolerant control-by-light.TM. distributed
intelligence system for sensing and control across fault tolerant fiber optic
networks. The system 10 uses the distributed local intelligent nodes 12-20 to
sense and/or control physical parameters and actuators with messages being
passed across redundant serial buses 21,22,23 whenever sense or control
information changes. In order to achieve fault tolerant operation, two, three
or four or more redundant data buses are employed depending upon the
criticality, and redundancy is also employed in certain intelligent nodes
performing critical functions such as sensor/actuator functions in an aircraft
control system. The coupling of the nodes 12-20 to the serial data buses is
accomplished by transceivers 26.sub.1-N and each transceiver 26.sub.1-N is
connected to a digital control and communication processor (DCCP) 28.sub.1-N.
Each combination of a transceiver and a DCCP may be referred to as a processing
element. This system 10 in an aircraft application replaces mechanical,
hydraulic and electrical controls now used by aircraft pilots to control,
monitor, and display primary and secondary flight control functions and it
provides substantial weight, cost, safety and performance advantages over
current techniques. This system 10 is applicable to control of other systems
besides aircraft such as ground transportation, surface and submarine ships,
spacecraft, utilities and industrial process controls. Although the data bus
media in the present preferred embodiment is implemented with fiber optics, the
deterministic network protocol is applicable to other medias such as twisted
pair wiring and power lines.

US005809220A

United States Patent [19]

Morrison et al.

[11] Patent Number: 5,809,220

[45] Date of Patent: Sep. 15, 1998

[54] FAULT TOLERANT DISTRIBUTED CONTROL SYSTEM

[75] Inventors: Brian D. Morrison, Hopkinton; Craig E. Wienke, Holliston; Martin R. Buttes, North Grafton; Michael N. Robillard, Shrewsbury, all of Mass.

[73] Assignee: Raytheon Company, Lexington, Mass.

[21] Appl. No.: 504,941

[22] Filed: Jul. 20, 1995

[51] Int. Cl.⁶ G06F 11/00

[52] U.S. Cl. 395/182.1; 395/185.06

[58] Field of Search 395/160, 182.02, 395/183.06, 184.01, 182.09, 182.1, 185.08; 370/105, 105.4, 105.5, 371/47.1

[56] References Cited

U.S. PATENT DOCUMENTS

|			
4,209,838	6/1980	Alcorn, Jr. et al.	364/200
4,872,163	10/1989	Pollett et al.	370/94.1
4,907,232	3/1990	Harper et al.	371/36
4,918,690	4/1990	Markkula, Jr. et al.	370/94
4,939,778	7/1990	Markkula, Jr. et al.	370/94.3
4,941,143	7/1990	Twitty et al.	370/85.2
5,012,469	4/1991	Sardana	370/95.3
5,058,143	10/1991	Messenger	375/118
5,168,588	12/1992	Thayer et al.	395/725
5,170,401	12/1992	Mohr	371/37.1
5,197,697	3/1993	Lytle et al.	244/197
5,249,270	9/1993	Stewart et al.	395/200
5,297,143	3/1994	Fridrich et al.	370/85.3
5,307,349	4/1994	Shloss et al.	370/85.2
5,319,642	6/1994	Ota	370/85.5
5,327,432	7/1994	Zela Al Abedeen et al.	370/95.3
5,377,109	12/1994	Baker et al.	364/424.06

OTHER PUBLICATIONS

Sundberg, G. "Civil Air Transport A Fresh Look At Power-By-Wire And Fly-By-Light", National Aeronautics and Space Administration, Lewis Research Center, Cleveland,

Ohio 44135, U.S. Government work not protected by U.S. copyright, pp. 1365–1368.

Udd, E. and Varshneva, D. "Fly-by-Light", Proceedings SPIE—The International Society for Optical Engineering, vol. 2295, Jul. 27–28, 1995, San Diego, California, pp. 46–51.

Hughes, D. "Raytheon/Beech Pursue Low-Cost Fly-By-Light", Aviation Week & Space Technology, Aviation Week Pilot Report Lockheed F-16 MATV, Raytheon/Beech Develop Fly-By-Light, May 2, 1994, pp. 51–55.

Kandebo, S. "NASA, Navy to Evaluate Fly-By-Light Sensors in F/A-18", Aviation Week & Space Technology, Aug. 2, 1993, pp. 55–56.

Morrison, B. "Flight Test of a Low-Cost Distributed Control-By-Light System", Journal of ATC, Jan.–Mar. 1995, pp. 21–23.

Todd, J. "Development of Fly-By-Light Systems", Douglas Aircraft Company McDonnell Douglas Corp., Long Beach CA: SPIE vol. 1173 Fiber Optic Systems for Mobile Platforms III, 1989, p. 139–146.

Palumbo, D. "A Low Maintenance and Highly Reliable Fly-By-Light Architecture", NASA Langley Research Center, pp. 477–481.

Primary Examiner—Robert W. Beausoliel, Jr.
Assistant Examiner—Joseph E. Palys
Attorney, Agent, or Firm—Donald F. Mofford

[57]   ABSTRACT

A fault tolerant distributed intelligence control system for sensing and control across fault tolerant fiber optic communication media interconnecting a plurality of intelligent nodes. Each intelligent node comprises a digital control and communication processor (DCCP) operating autonomously in relation to DCCPs at other nodes, and a transceiver for interfacing with the communication media. The fiber optic communication media comprises bi-directional serial data buses. The combination provides a low cost highly reliable distributed control system particularly applicable to primary and secondary aircraft control systems, as well as to other vehicle and control systems.

16 Claims, 7 Drawing Sheets

File Edit View Tools Window Help

US-PAT-NO: 4158208

DOCUMENT-IDENTIFIER: US 4158208 A

TITLE: Automatic setup system for television cameras

---------- KWIC ----------

 Detailed Description Text - DETX (29):
    The encoder 166 comprises four such up/down counters or accumulators 166a,
166b, 166c and 166d which four accumulator outputs are sequentially provided
each field to the gate 159 in response to gating signals sent via four leads
158 from commutator 157. Each of the leads 158 are coupled to a gating input
of a different one of the accumulators. The commutator 157 is responsive to
the vertical sync signal for sequentially gating during each field the four
addresses selected by the primary and monitoring buttons and for gating the
data in the appropriate accumulator and for gating the repeat address following
the data. If no data is present (no change in the knobs) a signal from that
up/down counter or accumulator is sent via one of the four leads 162 to the
commutator 157 to stop the repeat address. The data from the encoder 166 is in
the form of an 8-bit code which is provided sequentially from the impulse
up/down counters 166a through 166d to the gate 159. The commutator 157
provides a stop counter signal to the up/down counters or accumulators after
the first address. The commutator 157 sequences the impulse up/down counters
or accumulators 166a through 166d output during each field and provides a clear
to these counters at the end of each field. The display ROM 160 is responsive
to the 5-bit word from the primary function buttons and provides four addresses
to the alphanumeric character generator 161. The alphanumeric character
generator 161 is coupled to the appropriate display 163 to indicate the primary
functions controlled by the knobs. The secondary information (i.e. from the
red, green, blue, horizontal and vertical buttons) is indicated by the lighting
of the buttons. The alphanumeric display 163 can be flashed when there is an
out of range condition in the correction. For example, when the data out of
the adder/subtractor 113 in FIG. 8 is near zero or 256, the reverse data in the
serial bit stream is detected at detector 165 via gate 167 and is coupled to
display generator 161. When the red, green or blue switches 129, 130 and 131
are depressed, this is encoded in the 1 bit per line encoder 170 which provides
a logic "1" or "0" out of gate 167 during the setup control unit switch
function interval. This switch output is also directly coupled to the
monitors. Similarly, the waveform monitor switch buttons are coupled to
encoder 170 which provides the 1 bit per line code during the setup control
unit switch function interval to the camera processor. Similarly, the
condition switch functions indicated by some of the top buttons on the panel
are placed on the output data bus by being applied to encoder 170 and applied
to gate 167. The mode switch buttons are coupled to an encoder 176 which sends
a code to a function ROM 177 which identifies the mode switch being depressed.
The function ROM 177 when a code is applied provides an 8-bit address, 8-bit
data of all logic "1" or all "0" followed by a repeat address to gate 167

United States Patent [19]

Dischert

[11]   **4,158,208**

[45]   **Jun. 12, 1979**

3,730,984	5/1973	Smith	351/10 X
3,916,436	10/1975	Matey et al.	358/1
4,123,782	10/1978	Kimbara et al.	358/185 X

[54] **AUTOMATIC SETUP SYSTEM FOR TELEVISION CAMERAS**

[75] Inventor: Robert A. Dischert, Burlington, N.J.

[73] Assignee: RCA Corporation, New York, N.Y.

[21] Appl. No.: 894,098

[22] Filed: Apr. 6, 1978

[30]   **Foreign Application Priority Data**

May 30, 1977 [GB]   United Kingdom 22811/77

[51] Int. Cl.² H04N 9/62; H04N 9/04

[52] U.S. Cl. 358/10; 358/41; 358/185

[58] Field of Search 358/10, 41, 185

[56]   **References Cited**

U.S. PATENT DOCUMENTS

| 3,215,774 | 11/1965 | Bregani | 178/6.8 |
| 3,461,962 | 8/1969 | Bazin | 315/24 |

Primary Examiner—Robert L. Richardson

Attorney, Agent, or Firm—Eugene M. Whitacre; Paul J. Rasmussen; Robert L. Troike

[57]   **ABSTRACT**

An automatic setup unit for use with color TV cameras of the type including a digital memory for storing the control values for the camera. An automatic setup unit which is responsive to the video from the camera when viewing a predetermined pattern, such as a chart for measuring errors, is coupled to the memory and provides control signals to the memory with the appropriate addresses for updating the memory and for applying the control values to the camera.

7 Claims, 14 Drawing Figures

☐ ▓▓▓▓ Generate Collection ▓▓▓ | Print |

L3: Entry 4 of 6   File: USPT   Aug 21, 2001

DOCUMENT-IDENTIFIER: US 6279037 B1
TITLE: Methods and apparatus for collecting, storing, processing and using network traffic data

Brief Summary Text (14):
In order to facilitate the monitoring of network activity, remote monitoring (RMON) devices,
often called monitors or probes, are sometimes used. These devices often serve as agents of a
central network management station. Often the remote probes are stand-alone devices which
include internal resources, e.g., data storage and processing resources, used to collect,
process and forward, e.g., to the network management system, information on packets being
passed over the network segment being monitored. In other cases, probes are built into devices
such as a routers and bridges. In such cases, the available data processing and storage
resources are often shared between a device's primary functions and its secondary traffic
monitoring and reporting functions. In order to manage an intranet or other network comprising
multiple segments many probes may be used, e.g., one per each network segment to be monitored.

Current US Original Classification (1):
709/224

L3: Entry 5 of 6   File: USPT   Aug 11, 1998

DOCUMENT-IDENTIFIER: US 5793963 A
TITLE: Apparatus for providing non-redundant secondary access to field devices in a distributed
control system

Detailed Description Text (11):
More recently, field devices have been provided with microprocessors and additional
functionality. Such "smart" field devices are capable of monitoring a plurality of process
variables, performing a variety of control functions, performing comprehensive diagnostics, and
providing a wide array of various types of status information. The Fieldbus specification
specifies a variety of primary functions that may be supported by various Fieldbus field
devices. In addition, many manufacturers have provided secondary functions beyond those
specified in the Fieldbus specification. While Fieldbus field devices manufactured by different
manufacturers are compatible to the extent that only Fieldbus specified functions are accessed,
they are not compatible with respect to the secondary functions. For example, a Fieldbus
controller manufactured by company A will generally not be able to access the secondary
functions provided by a Fieldbus valve positioner manufactured by company B. Therefore, an
industrial plant using a variety of Fieldbus components provided by different manufacturers
will not be able to derive the benefit of all the functions provided by the various components.

Current US Cross Reference Classification (1):
709/217

Current US Cross Reference Classification (2):
709/224

☐ [Generate Collection] [Print]

L3: Entry 5 of 6   File: USPT   Aug 11, 1998

US-PAT-NO: 5793963
DOCUMENT-IDENTIFIER: US 5793963 A

TITLE: Apparatus for providing non-redundant secondary access to field devices in a distributed control system

DATE-ISSUED: August 11, 1998

INVENTOR-INFORMATION:
NAME	CITY	STATE	ZIP CODE	COUNTRY
Tapperson; Gary	Austin	TX		
Boyd; Thomas Andrew	Austin	TX		

ASSIGNEE-INFORMATION:
NAME	CITY	STATE	ZIP CODE	COUNTRY	TYPE CODE
Fisher Rosemount Systems, Inc.	Austin	TX			02

APPL-NO: 08/ 893126   [PALM]
DATE FILED: July 15, 1997

PARENT-CASE:
This is a continuation of application Ser. No. 08/328,324, filed Oct. 24, 1994 now abandoned.

INT-CL: [06] G06 F 11/30

US-CL-ISSUED: 395/200.31; 395/200.54, 395/200.47
US-CL-CURRENT: 709/201; 709/217, 709/224

FIELD-OF-SEARCH: 395/200.31, 395/200.54, 395/200.47

PRIOR-ART-DISCLOSED:

U.S. PATENT DOCUMENTS

[Search Selected] [Search ALL] [Clear]

	PAT-NO	ISSUE-DATE	PATENTEE-NAME	US-CL
☐	4149237	April 1979	Freitas	364/138
☐	4152760	May 1979	Freitai et al.	364/107
☐	4268822	May 1981	Olsen	340/533
☐	4303973	December 1981	Williamson, Jr. et al.	364/103
☐	4726017	February 1988	Krum et al.	370/85
☐	4729091	March 1988	Freeman et al.	
☐	4910658	March 1990	Dudash et al.	364/138
	4916441	April 1990	Gombrich	340/712

☐	5088021	February 1992	McLauglin et al.	364/187
☐	5099444	March 1992	Wilson et al.	364/709.09
☐	5131019	July 1992	Sheffer et al.	379/39
☐	5142550	August 1992	Tymes	375/1
☐	5150363	September 1992	Mitchell	370/112
☐	5239662	August 1993	Danielson et al.	395/800
☐	5374231	December 1994	Obrist	483/15
☐	5400246	March 1995	Wilson et al.	364/146
☐	5451923	September 1995	Seberger et al.	340/310.06
☐	5493569	February 1996	Buchholz et al.	370/85.7
☐	5495482	February 1996	White et al.	370/85.11
☐	5495484	February 1996	Self et al.	370/110.1

FOREIGN PATENT DOCUMENTS

FOREIGN-PAT-NO	PUBN-DATE	COUNTRY	US-CL
0 491 657 A1	June 1992	EP	
216109	August 1989	NZ	
227231	January 1991	NZ	
239534	November 1993	NZ	

OTHER PUBLICATIONS

D.A. Roberts, "`Olchfa` A Distributed Time-Critical Fieldsou", IEE, UK, London, Digest No: 1993/189, Oct./93 pp. 6/1-6/3.

ART-UNIT: 232

PRIMARY-EXAMINER: Geckil; Mehmet B.

ATTY-AGENT-FIRM: Kinney & Lange, P.A.

ABSTRACT:

An apparatus for accessing field devices in a distributed control system provides non-redundant secondary access to a plurality of field devices that are controlled by a control room. The field devices are coupled to a Fieldbus control network. In a first embodiment, each field device is provided with a wireless Fieldbus port that is accessible by a wireless handheld unit or wireless terminal. In a second embodiment, each Fieldbus control network is provided with a field module having a wireless Fieldbus port that allows all devices connected to the Fieldbus control network to be accessed by a wireless handheld unit or a wireless terminal. In a third embodiment, an H2-to-H1 Fieldbus bridge (which may service a plurality of H1 control networks) is provided with a wireless Fieldbus port that allows all Fieldbus devices connected to H1 control networks serviced by the H2-to-H1 bridge to be access by a wireless handheld unit of a wireless terminal. In a fourth embodiment, a bridge/converter provides an interface between older analog control room components and newer Fieldbus field devices. In one configuration, the bridge/converter includes a hard-wired Fieldbus port connected to a terminal, which may be in the control room. In another configuration, the bridge/converter includes a wireless Fieldbus port that allows a wireless handheld unit or a wireless terminal to access the Fieldbus devices serviced by the bridge/converter. The present invention allows a maintenance person to access Fieldbus field devices while servicing a device in the field, and allows

secondary functions of field devices (which vary by manufacturer) to be accessed from a single remote unit.

27 Claims, 3 Drawing figures

☐   Generate Collection | Print |

L3: Entry 6 of 6   File: USPT   Dec 16, 1997

DOCUMENT-IDENTIFIER: US 5699348 A
TITLE: Method and apparatus for error performance monitoring of a leased telecommunication
circuit

Brief Summary Text (8):
The present invention relates to a method and apparatus for use in monitoring and analyzing
statistical parameters corresponding to errors occurring in the transmission of data signals in
a telecommunication system. Communication between two customer sites preferably occurs through
the use of a leased line or circuit, which defines fixed paths between the customer terminals
and which comprises a plurality of transmission media and a plurality of network elements,
including a near end and a far end network element. Each network element preferably comprises a
primary and secondary port, each of which functions in one of a plurality of modes, for
example, a first mode, a second mode, or a third mode. According to one embodiment, each port
is in either a terminated mode, a framed clear mode, or an unframed clear mode. Errors in the
transmission of data signals are detected and collected in at least some of the ports each of
which preferably processes the data it collects to produce statistical parameters such as
errored-seconds or severely-errored-seconds. The statistical parameters are then sent to a
central management system which executes a performance monitoring ("PM") count routine to
determine the number of errored-seconds, or severely-errored-seconds, associated with each
direction of transmission in the customer circuit.

Current US Cross Reference Classification (1):
370/252

Previous Doc   Next Doc   Go to Doc#

☐   Generate Collection   Print

L3: Entry 6 of 6   File: USPT   Dec 16, 1997

US-PAT-NO: 5699348
DOCUMENT-IDENTIFIER: US 5699348 A

TITLE: Method and apparatus for error performance monitoring of a leased telecommunication
circuit

DATE-ISSUED: December 16, 1997

INVENTOR-INFORMATION:
NAME	CITY	STATE	ZIP CODE	COUNTRY
Baidon; Sami A.	New Milford	NJ		
Huang; Shirley L.	Holmdel	NJ		

ASSIGNEE-INFORMATION:
NAME	CITY	STATE	ZIP CODE	COUNTRY	TYPE CODE
Lucent Technologies Inc.	Murray Hill	NJ			02

APPL-NO: 08/ 551136   [PALM]
DATE FILED: October 31, 1995

INT-CL: [06] H04 J 3/14

US-CL-ISSUED: 370/242; 370/252, 395/185.01
US-CL-CURRENT: 370/242; 370/252, 714/48

FIELD-OF-SEARCH: 370/242, 370/243, 370/244, 370/252, 379/10, 379/24, 379/26, 395/183.01,
395/185.01

PRIOR-ART-DISCLOSED:

U.S. PATENT DOCUMENTS

Search Selected   Search ALL   Clear

	PAT-NO	ISSUE-DATE	PATENTEE-NAME	US-CL
☐	4730313	March 1988	Stephenson et al.	
☐	5099511	March 1992	Matsumoto	379/198
☐	5148426	September 1992	Shenoi et al.	370/32.1
☐	5166890	November 1992	Smischny	364/551.01
☐	5233648	August 1993	Nakamura	379/233
☐	5311586	May 1994	Bogard et al.	379/221
☐	5327489	July 1994	Anderson et al.	379/207
☐	5329520	July 1994	Richardson	370/16

☐	5329589	July 1994	Fraser et al.	379/91
☐	5343461	August 1994	Barton et al.	370/13
☐	5400266	March 1995	Sato et al.	364/550
☐	5450441	September 1995	Harris et al.	375/224
☐	5513173	April 1996	Machemer et al.	370/252
☐	5528748	June 1996	Wallace	395/183.01

OTHER PUBLICATIONS

Gerald D. Austin and Hilary B. Tomasson, "Unlocking the Value of Performance Monitoring Data," Telephony, Nov. 14, 1994, pp. 49-52.

ART-UNIT: 263

PRIMARY-EXAMINER: Olms; Douglas W.

ASSISTANT-EXAMINER: Jung; Min

ABSTRACT:

A method and apparatus for use in monitoring and analyzing statistical parameters corresponding to errors occurring in the transmission of data signals in a telecommunications network is disclosed. Communication between two customer sites occurs through the use of a leased line or circuit, which defines fixed paths between the customer terminals and which comprises a plurality of network elements. Statistical parameters, corresponding to errors detected and processed at ports in the network elements, are sent to a central management system which executes a performance monitoring count routine to determine the total number of errored-seconds, or severely-errored-seconds, or other statistical parameters associated with each direction of transmission in the customer circuit.

12 Claims, 5 Drawing figures

Hit List

| Clear | Generate Collection | Print | Fwd Refs | Bkwd Refs | Generate OACS |

Search Results - Record(s) 1 through 2 of 2 returned.

☐ 1.   Document ID: JP 59008005 A

L1: Entry 1 of 2   File: JPAB   Jan 17, 1984

PUB-NO: JP359008005A
DOCUMENT-IDENTIFIER: JP 59008005 A
TITLE: MULTIPLEXING DEVICE

| Full | Title | Citation | Front | Review | Classification | Date | Reference | | | Claims | KWIC | Draw Desc | Image |

☐ 2.   Document ID: EP 1523826 A1, WO 2004010645 A1, US 20040139264 A1, AU 2003250959 A1

L1: Entry 2 of 2   File: DWPI   Apr 20, 2005

DERWENT-ACC-NO: 2004-143624
DERWENT-WEEK: 200527
COPYRIGHT 2005 DERWENT INFORMATION LTD

TITLE: Communications bus station provides <u>secondary bus monitoring function</u> in addition to its <u>primary function</u>

| Full | Title | Citation | Front | Review | Classification | Date | Reference | | | Claims | KWIC | Draw Desc | Clip Img | Ima |

| Clear | Generate Collection | Print | Fwd Refs | Bkwd Refs | Generate OACS |

Terms	Documents
(primary adj1 function) same (secondary adj5 function) same monitor$3	2

Display Format: | - | | Change Format |

Previous Page   Next Page   Go to Doc#

☐   ▓▓ Generate Collection ▓▓ | Print |

L1: Entry 2 of 2   File: DWPI   Apr 20, 2005

DERWENT-ACC-NO: 2004-143624
DERWENT-WEEK: 200527
COPYRIGHT 2005 DERWENT INFORMATION LTD

TITLE: Communications bus station provides secondary bus monitoring function in addition to its primary function

INVENTOR: FAIST, F; GROS, T

PATENT-ASSIGNEE: VEGA GRIESHABER KG (VEGAN), FAIST F (FAISI), GROS T (GROSI)

PRIORITY-DATA: 2002US-397558P (July 18, 2002), 2003US-0623199 (July 18, 2003)

| ▓ Search Selected ▓ | ▓ Search ALL ▓ | ▓ Clear ▓ |

PATENT-FAMILY:

	PUB-NO	PUB-DATE	LANGUAGE	PAGES	MAIN-IPC
☐	EP 1523826 A1	April 20, 2005	G	000	H04L012/24
☐	WO 2004010645 A1	January 29, 2004	G	043	H04L012/24
☐	US 20040139264 A1	July 15, 2004		000	G06F013/14
☐	AU 2003250959 A1	February 9, 2004		000	H04L012/24

DESIGNATED-STATES: AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LT LU LV MC MK NL PT RO SE SI SK TR AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CO CR CU CZ DE DK DM DZ EC EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NI NO NZ OM PG PH PL PT RO RU SC SD SE SG SK SL SY TJ TM TN TR TT TZ UA UG US UZ VC VN YU ZA ZM ZW AT BE BG CH CY CZ DE DK EA EE ES FI FR GB GH GM GR HU IE IT KE LS LU MC MW MZ NL OA PT RO SD SE SI SK SL SZ TR TZ UG ZM ZW

APPLICATION-DATA:

PUB-NO	APPL-DATE	APPL-NO	DESCRIPTOR
EP 1523826A1	July 15, 2003	2003EP-0764993	
EP 1523826A1	July 15, 2003	2003WO-EP07666	
EP 1523826A1		WO2004010645	Based on
WO2004010645A1	July 15, 2003	2003WO-EP07666	
US20040139264A1	July 18, 2002	2002US-397558P	Provisional
US20040139264A1	July 18, 2003	2003US-0623199	
AU2003250959A1	July 15, 2003	2003AU-0250959	
AU2003250959A1		WO2004010645	Based on

INT-CL (IPC): G06 F 13/14; H04 L 12/24; H04 L 12/26; H04 L 12/40

ABSTRACTED-PUB-NO: WO2004010645A
BASIC-ABSTRACT:

NOVELTY - The bus station, e.g. a sensor (14), actuator (15) or gateway (23), performs a secondary bus monitoring function in addition to its primary function via an integrated bus monitor device (30) allowing access to telegram traffic along the bus system (5), for recording and reprocessing. The bus stations are connected in a network allowing monitoring of the bus system via the bus stations.

DETAILED DESCRIPTION - Also included are INDEPENDENT CLAIMS for the following:

(a) a network with a bus system and at least one bus station;

(b) a method for monitoring a bus system

USE - The communications bus station is used performing a primary function and for monitoring the bus system.

ADVANTAGE - Existing bus stations are utilized for providing bus system monitoring function.

DESCRIPTION OF DRAWING(S) - The figure shows a schematic representation of a bus system with integrated bus monitoring function in bus stations.

Bus system 5

Sensor 14

Actuator 15

Gateway 23

Bus monitor device 30

ABSTRACTED-PUB-NO: WO2004010645A
EQUIVALENT-ABSTRACTS:

CHOSEN-DRAWING: Dwg.7/10

DERWENT-CLASS: W01
EPI-CODES: W01-A06A; W01-A06B1;